




Job Name: _____

Date: _____ Location: _____

Notes: _____

1616, 45° Surface Mount LED Strip Fixture



• Product Description

Prefabricated LED strip fixtures including lens, end caps, mounting hardware and lead wire.

• Installation Applications

Coves, cabinetry, display cases, stairwells, toe kicks.

• Product Features

- Anodized aluminum channel allows for heat dissipation and extended LED life.
- Diffused polycarbonate lens.
- Mountable on any flat surface.
- Continuous diode free illumination .
- Maintenance free.
- Silent operation.
- UV light and IR radiation free.

Product Specifications

Application Type	Surface mount
Size (LXWXH)	10.5"- 45.8" X 0.63" X 0.68"
Input Voltage	24V DC constant voltage
Power	4W - 16W
CCT	3000K, 3500K, 4000K
Lumens	As page 2
Beam Angle	45 °
CRI	85+
Dimmable	Yes
Lead Wire	7.87"
IP Rating	IP 20 (Indoor)
Rated Life	50,000 hours
Operating Temp.	-30 to 75°C
Mounting	Snap in clips provided
Electrical Approval	
Warranty	5 Years

ORDERING OPTIONS

ITEM #	LENGTH	CCT	LUMENS
SF1616-24-12-4-30-SL	10.50"	3000K	300lm
SF1616-24-12-4-35-SL	10.50"	3500K	315lm
SF1616-24-12-4-40-SL	10.50"	4000K	330lm
SF1616-24-24-8-30-SL	22.31"	3000K	600lm
SF1616-24-24-8-35-SL	22.31"	3500K	630lm
SF1616-24-24-8-40-SL	22.31"	4000K	660lm
SF1616-24-36-12-30-SL	34.12"	3000K	900lm
SF1616-24-36-12-35-SL	34.12"	3500K	945lm
SF1616-24-36-12-40-SL	34.12"	4000K	990lm
SF1616-24-48-16-30-SL	45.81"	3000K	1200lm
SF1616-24-48-16-35-SL	45.81"	3500K	1260lm
SF1616-24-48-16-40-SL	45.81"	4000K	1320lm