



Job Name: _____

Date: _____ Location: _____

Notes: _____

LOW POWER LED SMD2835 TAPE LIGHT



PRODUCT CODE

TP2835-5M1020-2W2427	(2700K)
TP2835-5M1020-2W2430	(3000K)
TP2835-5M1020-2W2435	(3500K)
TP2835-5M1020-2W2440	(4000K)
TP2835-5M1020-2W2450	(5000K)

PRODUCT SPECIFICATIONS

• Lighting Applications

Accent and Task lighting

• Installation Applications

Coves, cabinetry, display cases, stairwells, toe kicks




• Product Features

- Cost effective
- Reliable performance
- Silent operation
- Maintenance free
- Field cuttable and bridgeable
- UV light and IR radiation free
- Dimmable when used with dimmable power supply (sold separate)

Size (LXWXH)	5M X 10mm X 1.6mm
LED Type	SMD2835
Input Voltage	24V DC, constant voltage
Power	6W/M, 1.8W/FT
LED per Meter	120
CCT	2700K, 3000K, 3500K, 4000K, 5000K
Lumens	Up to 650LM/M, 200LM/FT
Beam Angle	120°
CRI	90+
Dimmable	Yes
Installation	3M adhesive backing
Connection	20AWG, 200mm lead both ends
IP Rating	IP20 (Indoor)
Rated Life	50,000 hrs
Operating Temp.	-30~75°C
Electrical Approval	cULus
Warranty	5 years

Dimensions & available lengths

Illuminance Distribution



COMPATIBLE CONNECTORS AND MOUNTING CLIPS



HIPPO CLIP

10mm IP20 (5pk)

AL-TCP-HC-STW-10-20 STRIP TO WIRE

AL-TCP-HC-STS-10-20 STRIP TO STRIP




BEETLE CLIP

10mm IP20 (10pk)

AL-TCP-BC-STW-10-20 STRIP TO WIRE

AL-TCP-BC-STS-10-20 STRIP TO STRIP




SOLID LOCK CLIP

10mm IP20 (10pk)

AL-TCP-SL-STW-10-20 STRIP TO WIRE

AL-TCP-SL-STS-10-20 STRIP TO STRIP



FPC L SHAPE CONNECTOR

10mm IP20 (3pk)

AL-TCP-FPC-L-10-20 STRIP TO STRIP



FPC T SHAPE CONNECTOR

10mm IP20 (3pk)

AL-TCP-FPC-T-10-20 STRIP TO STRIP



FPC CROSS CONNECTOR

10mm IP20 (3pk)

AL-TCP-FPC-C-10-20 STRIP TO STRIP



MOUNTING CLIPS

10mm (10pk)

AL-TCP-MC-10

COMPATIBLE DIMMABLE LED POWER SUPPLIES



40W HARDWIRE DRIVER

DVR-HWB-CV-24VDC-40W



96W HARDWIRE DRIVER

DVR-HWB-CV-24VDC-96W



200W HARDWIRE DRIVER

DVR-HWB-CV-24VDC-200W