

HIGH POWER LED COB TAPE LIGHT



PRODUCT CODE

TPCOB-5M1020-4W2427	(2700K)
TPCOB-5M1020-4W2430	(3000K)
TPCOB-5M1020-4W2435	(3500K)
TPCOB-5M1020-4W2440	(4000K)

PRODUCT SPECIFICATIONS

• Lighting Applications

Accent and Task lighting

• Installation Applications


Coves, cabinetry, display cases, stairwells, toe kicks

• Product Features


- Continuous diode free illumination
- Silent operation
- Maintenance free
- Field cuttable and bridgeable
- UV light and IR radiation free
- Dimmable when used with dimmable power supply (sold separate)

Size (LXWXH)	5M X 10mm X 1.6mm
LED Type	COB
Input Voltage	24V DC, constant voltage
Power	12W/M, 4.2W/FT
LED per Meter	480
CCT	2700K, 3000K, 3500K, 4000K
Lumens	Up to 1410LM/M, 430LM/FT
Beam Angle	180°
CRI	90+
Dimmable	Yes
Installation	3M adhesive backing
Connection	20AWG, 200mm lead both ends
IP Rating	IP20 (Indoor)
Rated Life	50,000 hrs
Operating Temp.	-30~75°C
Electrical Approval	cULus
Warranty	5 years

Dimensions & available lengths



Illuminance Distribution



COMPATIBLE CONNECTORS AND MOUNTING CLIPS



HIPPO CLIP

10mm IP20 (5pk)

AL-TCP-HC-STW-10-20 STRIP TO WIRE

AL-TCP-HC-STS-10-20 STRIP TO STRIP




BEETLE CLIP

10mm IP20 (10pk)

AL-TCP-BC-STW-10-20 STRIP TO WIRE

AL-TCP-BC-STS-10-20 STRIP TO STRIP




SOLID LOCK CLIP

10mm IP20 (10pk)

AL-TCP-SL-STW-10-20 STRIP TO WIRE

AL-TCP-SL-STS-10-20 STRIP TO STRIP



FPC L SHAPE CONNECTOR

10mm IP20 (3pk)

AL-TCP-FPC-L-10-20 STRIP TO STRIP



FPC T SHAPE CONNECTOR

10mm IP20 (3pk)

AL-TCP-FPC-T-10-20 STRIP TO STRIP



FPC CROSS CONNECTOR

10mm IP20 (3pk)

AL-TCP-FPC-C-10-20 STRIP TO STRIP



MOUNTING CLIPS

10mm (10pk)

AL-TCP-MC-10

COMPATIBLE DIMMABLE LED POWER SUPPLIES



40W HARDWIRE DRIVER

DVR-HWB-CV-24VDC-40W



96W HARDWIRE DRIVER

DVR-HWB-CV-24VDC-96W



200W HARDWIRE DRIVER

DVR-HWB-CV-24VDC-200W